

HIGH PERFORMANCE



RETRO PERFORMANCE MODULE

LED

LED MR-16 GU 5.3 BASE LED SERIES- YELLOW LINE

FEATURES AND BENEFITS:

- Designed in the USA
- Enclosed Outdoor Fixture Rated
- Damp Location Rated
- Energy Start Efficiency
- Available in 3W, 4W or 7W

Technical Specifications:

Power Consumption:	3W	4W	7W
Model Name:	RPM-3W12K27Y RPM-3W40K27Y RPM-3W60K27Y	RPM-4W12K27Y RPM-4W40K27Y RPM-4W60K27Y	RPM-7W12K27Y RPM-7W40K27Y RPM-7W60K27Y
Photo			
Halogen Equivalent:	20 Watt	30 Watt	50 Watt
Operating Voltage:	12VAC/DC Dimmable	12VAC/DC Dimmable	12VAC/DC Dimmable
Dimming Range:	15-100%	15-100%	15-100%
Dimensions:	1.93"Wx1.96"H	1.93"Wx1.96"H	1.93"Wx1.96"H
CRI:	> 80	> 80	> 80
Color Temperature:	2700K	2700K	2700K
Luminous Flux:	250 lumens	350 lumens	500 lumens
Lens Bin Option:	12°, 40°, 60°	12°, 40°, 60°	12°, 40°, 60°
Safety Certification:	UL	UL	UL
Rated Lifespan:	>25,000hrs	>25,000hrs	>25,000hrs

Notes: Wattage +/- 10%; Lumen Values +/- 5Lms; CRI +/- 5%; **Dimmable*** Fully test with the following dimmer models: Lutron S-300 LIGHTTECH LET 60LW, Lutron S-300 LIGHTTECH LET 75LW, Lutron SCL-153P, Leviton 6631, Lutron CTCL-153P, Lutron SCL0153P.