


P16 American Pagoda | Path Light

PRODUCT DESCRIPTION

Ideal for pathways, walkways, patios, and small areas.

The American Pagoda Series Path Lights feature an incredible 360° diffused light output. The P16 is low profile at just over 1.5 inches tall installed and comes with an LV130 stake.

PRODUCT DIMENSIONS & BEAM SPREAD



Patent pending

FEATURES & BENEFITS

- Built in the U.S.A.
- CNC-machined from 6061 aircraft-grade aluminum.
- U.S.A. made light engine and driver.
- Built in surge protector.
- IP66 rated.
- CREE 2 step binned LEDs with L70 over 80,000 hours.

SPECIFICATIONS

- 2.14" x 2.25" diameter
- Construction: 6061 aircraft-grade aluminum
- Finishes: Architectural Bronze (AB), Black (BLK), Stainless Aluminum (SSA)
- Lead Wire: 90" 22 AWG tinned copper
- Mounting: 8.5" LV130 ground stake
- Driver System: Internal
- Operating Voltage: 10.5-18 VAC
- CRI: 80+
- Beam Spread: 120°







SSA

AB

POWER CONSUMPTION

COLOR TEMPERATURE	WATTAGE	VA	LUMENS
<mark>- 3000K</mark> *	1W	2VA	115LM

ADDITIONAL COLOR TEMPERATURE OPTIONS

● 2700K ● 5000K** ● Amber** ● Blue** ● Royal Blue** ● Green** ● Red**

WARRANTY

20 Year Limited Warranty

CERTIFICATIONS



Tested to UL standards.

Intertek

*3000K is stocked item. 2700K is non-stocked item that requires 5-7 business days additional lead time, special order deposit and are non-refundable. **Special order only. Requires 5-7 business days additional lead time, special build fee, special order deposit, and are non-refundable.