


REV | Revolutionary Spotlight Interchangeable Integrated Technology

PRODUCT DESCRIPTION

Ideal for uplighting, shadowing, wall washing, silhouetting, and architectural accents.

This revolutionary tool-less spotlight simplifies upgradeability and maintenance of the luminaire, including the shroud, lens, sealing O-rings, optics and patented XRB-Drive (light engine and driver in one).

PRODUCT DIMENSIONS



FEATURES & BENEFITS


- Patented
- Built in the U.S.A.
- CNC-machined from 6061 aircraft-grade aluminum.
- U.S.A. made light engine and driver.
- Built in surge protector.
- Adjustable knuckle for ease of light positioning.
- Patented Interchangeable XRB-Drive with three power levels.
- Lock-and-load shroud completely prevents water intrusion
- Breathable ant guard to eliminate insect infestation.
- IP66 rated.
- CREE 2-step binned LEDs with L70 over 80,000 hours.

SPECIFICATIONS

- Construction: 6061 aircraft-grade aluminum
- Finishes: Architectural Bronze (AB), Black (BLK),
- Omega Black (OBLK)
- Lead Wire: 31" 20 AWG tinned copper
- Mounting: 8" LV130 ground stake
- Lens: Clear flat easily replaceable
- **Driver System:** Patented Internal XRB-Drive (light engine and driver in one)
- Operating Voltage: 10.5-18 VAC
 Beam Spreads: 12°, 40°, 60°



FIXTURE KIT



OPTIONAL SHROUDS AVAILABLE

34.5° Shroud 45° Shroud 58° Shroud JLM° Shroud

POWER CONSUMPTION

COLOR TEMPERATURE	WATTAGE	VA	LUMENS
3000K*	3W	4VA	315LM
	5W	6.4VA	541LM
	7W	9.8VA	777LM

ADDITIONAL COLOR TEMPERATURE OPTIONS

2700K

WARRANTY

20 Year Limited Warranty

CERTIFICATIONS



Tested to UL standards.

Intertek

*Indicates stocked items.

IES files can be found at www.gardenlightled.com