


P14 | Omega Black Path Light (Integrated LED)

PRODUCT DESCRIPTION

The P14 Path Light, in Omega Black finish, offers traditional style and durability for residential and commercial landscapes. CNC-machined from 6061 aircraft-grade aluminum, it features a corrosionresistant, scratch-proof shell for reliable performance in harsh conditions.

DDODUCT DINAENICIONS



FEATURES & BENEFITS

- Built in the U.S.A.
- CNC-machined from 6061 aircraft-grade aluminum.
- U.S.A. made light engine and driver.
- Built in surge protector.
- Breathable ant guard to eliminate insect infestation.
- Field serviceable and upgradeable LED board.
- CREE 2 step binned LEDs with L70 over 80,000 hours.
- IP66 rated.

SPECIFICATIONS

- Construction: 6061 aircraft-grade aluminum
- Finishes: Omega Black (OBLK)
- Lead Wire: 27" 18 AWG tinned copper
- Mounting: 8.5" LV131 ground stake
- Driver System: External
- Operating Voltage: 10.5-18 VAC
- CRI: 80+
- Beam Spread: Flood



POWER CONSUMPTION

COLOR TEMPERATURE	WATTAGE	VA	LUMENS
<u>– 3000К</u>	2W	4VA	TBD
ADDITIONAL COLOR TEMPERATURE OPTIONS			

2700K
5000K
Amber
Blue
Royal Blue
Green
Red

WARRANTY

20 Year Limited Warranty

CERTIFICATIONS



Tested to UL standards.

Intertek

*Indicates stocked items. Non-stocked items require 5-7 business days additional lead time, special order deposit and are non-refundable.