


PO-II | Path Light


PRODUCT DESCRIPTION

Ideal for pathways, walkways, patios, and small areas.

At only 2.5 inches tall, this powerful little low voltage LED light can wash a large horizontal surface of any outdoor landscape area. This is amongst our most modern and innovative outdoor lighting fixture for use in contemporary landscaping and architecture designs.

PRODUCT DIMENSIONS & BEAM SPREAD





FEATURES & BENEFITS

- Built in the U.S.A.
- CNC-machined from 6061 aircraft-grade aluminum or raw brass.
- U.S.A. made light engine and driver.
 - Built in surge protector.
- IP67 rated.
- CREE 2 step binned LEDs with L70 over 80,000 hours.

SPECIFICATIONS

- **Construction:** 6061 aircraft-grade aluminum or raw brass
- Finishes: Architectural Bronze (AB), Black (BLK), Stainless Aluminum (SSA), Brass (BR)
- Lead Wire: 60" 22 AWG tinned copper
 Mounting: 8.5" LV131 ground stake
- Driver System: Internal
- Operating Voltage: 10.5-18 VAC
- CRI: 80+
- Beam Spread: 120°









POWER CONSUMPTION

COLOR TEMPERATURE	WATTAGE	VA	LUMENS
3000K*	1W	2VA	115LM

ADDITIONAL COLOR TEMPERATURE OPTIONS



WARRANTY

20 Year Limited Warranty

CERTIFICATIONS



Tested to UL standards.

Intertek

*Indicates stocked items. Non-stocked items require 5-7 business days additional lead time, special order deposit and are non-refundable.

IES files can be found at www.gardenlightled.com